

High performance multi-point life safety panic and emergency exit bolting systems, automatically re-securing upon door closure, ensuring high level threat protection of forced entry, blast, ballistic and fire protection. The system secures with a vertical bolt at the top and bottom of the door.

Choice of active leaf entry includes key, access control, combination deadlocking, or motorised remote release. Meeting a wide range of international accreditations. Manufactured in 316 stainless steel for hostile environments and durability.

FEATURES

- Surface mounting
- 15mm (5/8") bolts x 25mm (1") throw
- 316 grade stainless steel construction for hostile environments and durability
- Proven rack & pinion driven
- Cycle tested to over 1,000,000 cycles

BENEFITS

- Automatic securing upon door closure
- Certified to a range of international standards (see Product Performance Chart)
- Engineered for longevity and trouble-free service

OPTIONAL ENHANCEMENTS

- Monitoring of bolt status
- Infinite 'iRestraint' restrains bolts throughout their opening travel
- Choice of exit device operators
- Selection of suitable keeps available
- Further enhancements are available

PRODUCT PERFORMANCE CHART

Indicates product has been certified, or tested & approved as part of a complete doorset assembly. Product certification is subject to the chosen lock configuration, for full details please contact the sales office.



SECURITY																SAFETY	BALLISTIC	BLAST	FIRE	CORROSION	CYCLES			
LPS 1175								LPS 1673 (AR.)					FEBR (min)	EN 1627	STS 202							PAS 24	LPS 2081	
Issue 7	SR1	SR2	SR3	SR4	SR5	SR6	SR7																	SR8
Issue 8	A	B	C	D	E	F	G	H	TIME	A	B	C	D											
20 MIN									300 SEC					60	RC6	BR6	PAS 24	SRB	EN 1125	EN 1522 FB7	ISO 16933 EXV 15	UL 10C	GR5	1 MIL
15 MIN									240 SEC						RC5	BR5			EN 179	UL 752 Level 10		EN 1634-1		GR4
10 MIN	A10	B10	C10	D10					180 SEC					15	RC4	BR4	SRA	UL 305	NIJ 0108.01 Level 1-4	ASTM F2927 Cat 1	Certifire BS 476-22	GR3	500K	
5 MIN									120 SEC						RC3	BR3						GR2		
3 MIN									60 SEC					5	RC2	BR2						GR1		
1 MIN									30 SEC						RC1	BR1							200K	



EXAMPLE PRODUCT CODES

Active leaf (Right side):
SL3C-XXXX-AB-LMPB-XX-A07Y01

Passive leaf (Left side):
SL2A-XXXX-AB-LMPB-XX-A07