

The Palisade Pedestrian is a heavy-duty manual sliding-bar locking system for hinged gates with 50 mm (2") engagement. Engineered to offer multiple entry and exit methods, the range is versatile and suitable for most applications.

Entry methods include key or access control with manual slide bar release. A choice of controlled or single-motion egress for emergency exits is available to meet a wide range of requirements. Manufactured in Grade 316 stainless steel for hostile environments and durability.



FEATURES

- Surface-mounted for maximum strength
- 50 mm (2") x 12 mm (1/2") sliding bar with a 50 mm (2") throw
- Choice of automatic or manual deadlocking
- Grade 316 stainless steel construction for hostile environments and durability
- Independent padlocking
- Tested to over 1,000,000 cycles
- To suit rim profile cylinders (order cylinder separately)
- 12V DC as standard

BENEFITS

- Tested and certified to LPS 1175: Issue 8 Security Rating D10
- Engineered for longevity and trouble-free service
- Retrofittable solution to upgrade existing gates

OPTIONAL ENHANCEMENTS


- Monitoring of bolt & lock status
- Cylinder guard protection available from our tested and accredited range
- Breakdome over thumbturn and lever handle to control exit
- 24V DC fail secure, 12V DC or 24V DC fail safe
- Further enhancements are available

PRODUCT PERFORMANCE CHART

☐ Indicates product has been certified, or tested & approved as part of a complete doorset assembly.
Product certification is subject to the chosen lock configuration, for full details please contact the sales office.

SECURITY															SAFETY	BALLISTIC	BLAST	FIRE	CORROSION	CYCLES					
LPS 1175								LPS 1673 (AR.)					FEBR (min)	EN 1627							STS 202	PAS 24	LPS 2081		
Issue 7	SR1	SR2	SR3	SR4	SR5	SR6	SR7																	SR8	
Issue 8	A	B	C	D	E	F	G	H	TIME	A	B	C	D												
20 MIN									300 SEC					60	RC6	BR6	PAS 24	SRB	EN 1125	EN1522 FB1-7	ISO 16933 EXV 15/25	UL 10C	GR5	1 MIL	
15 MIN									240 SEC						RC5	BR5									
10 MIN	A10	B10	C10	D10					180 SEC					15	RC4	BR4	SRA	UL 305	EN 179	UL752 Level 1-10	ASTM F2927 Cat 1	EN 1634-1	GR4	500K	
5 MIN									120 SEC						RC3	BR3								CERTIFIRE	GR3
3 MIN									60 SEC					5	RC2	BR2								GR2	200K
1 MIN									30 SEC						RC1	BR1							BS 476-22	GR1	


PALISADE PEDESTRIAN TECHNICAL DRAWINGS



SELF CODING SYSTEM

The Palisade Pedestrian (PP) has a simple ordering code that covers the chosen methods of entry and exit, followed by the mounting and orientation codes. Additional enhancements can be added to further customise the device.

EXAMPLE ORDER CODE: PP1A-KMSK-MA-LMSK



PRODUCT			ENTRY		SECURING		EXIT		
RANGE		BOLTS	UNLOCKING		UPON DOOR CLOSURE		UNLOCKING		
PP	Palisade Pedestrian	1	X	None	MA	Manual bolting / auto deadlocking	X	None	
BOLT DIRECTION			K	Key	MM	Manual bolting / manual deadlocking	K	Key	
A	Horizontal bolt		A	Access control			A	Access control	
		BOLT RETRACTION		T			Thumbturn		
		X	None	L			Single operation		
		M	Manual	BOLT RETRACTION					
		OPERATOR		X			None		
		XX	None	M			Manual		
		KH	Knob handle	OPERATOR					
							XX	None	
							KH	Knob handle	

EXAMPLE BOLT DIRECTIONS

See coding chart above for reference



Number of Bolts (1)
Direction (A)